

# 2000-V21 Hydraulic Shower Trolleys

EZ Way, Inc.

## Multi-tasking shower trolley with endless application possibilities

The 2000-V21 hydraulic, foot-operated shower trolley is unique with its side mounted column allowing the trolley stretcher to overlap the bed further for a safe and easy patient transfer. It has a patient weight capacity of 440 lb. (200 kg).

The trolley drains at both ends allowing the person to be positioned in either direction, an invaluable feature for the caregiver.

The 2000-V21 comes in four sizes. Three models have 25 in. width, and are available in 63 in., 75 in., or 83 in. lengths. A wider model (27.4 in. wide x 77 in. long) is available if there is a need for an increased patient working area.

The 2000-V21 height adjustable Shower Trolley is a great solution to prevent back injuries ,and to minimize static load and offers a safe and ergonomic working environment for the caregiver.

(6

Registered at Medical Products Agency, Sweden, as a MD Class 1 product, MDR 2017/745.

TR reserves the right to make design changes and/or improvements without notice.



#### **Specifications**

Length: (4 models)	Standard = 75 in. (1900 mm), Short = 63 in. (1600 mm), Long= 83 in. (2100 mm) Wide = 76.8 in. (1950 mm)	
Width:	Standard, Short, Long = 25 in. (640 mm). Wide = 27.4 in (695 mm)	
Height:	Min. 23.62 in. (600 mm), Max. 35.4 in. (900 mm)	
Max Patient weight:	440 lb. (200 kg)	
Chassis/Frames:	Powder coated stainless steel	
Floor clearance:	6.3 in. (160 mm) (height of the base allows mobile sling lift transfers)	
Castors:	4 Braked twin castors, 4 in. (100 mm) as standard (Straight Steering castors optional)	
Control:	Foot operated control for height and manual tilt adjustment on both sides	
Mattress, pillow:	Blue, both in flame retardant material, Mattress with Dual drainage	
Tilt:	Manual tilt adjustment on both sides, +/- 4 degrees	
Battery:	On board 24 V , 7 Ah. / Removable LiON 24 V, 5 Ah. Buzzer for low battery	
Protection Class Electronics:	Complete unit IPX5 (Handcontrol and removable batteries IPX6)	Form #2-365 1/11/23

#### **Features**

- Quiet and smooth height/tilt adjustable motion.
- Designed for easy cleaning and ease in mobility.
- The mattress is easily removable.
- Side mounted column for improved patient transfers.
- Foldable side rails for efficient and safe patient transfer and transport.
- Maximum patient weight of 440 lb. (200 kg.).
- 4 different models of 2000-V21 available to find most suitable size for resident and care environments.
- Dual drainage offers easy change of designated head end.
- The side rails can be pressed together traveling through narrow doorways.
- Floor clearance at 6.3 in. (160 mm) to enable floor lift transfers.
- The stretcher can easily be tilted in both directions to the "Trendelenburg" position, to alleviate person in shock.
- The chassis and sub-frames are made of powder coated stainless steel.
- The stretcher has rubber bumper wheels on all four corners to protect walls and doorways.



Foot control

Comes with four, 4 in. (100 mm) braked twin castors as standard.

Straight steering option available.

- Proven choice of durable high quality components, guarantees a low cost of ownership.
- All models come with mattress, head pillow, 4 braked castors and 3 ft. (1 m) flexible drainage hose with hose holder as standard.

### **Accessories/Options**

- Backrest wedge pillow, 15°. Blue, grey or yellow. Backrest wedge pillow, 30°. Grey (2000W-V21)
- All models can be delivered with grey or yellow head pillow instead of blue (standard)
- Fastners/straps for attachment on mattresses to siderails.
- Longer drainage hose 8 feet, instead of 3 feet as standard.
- Straight steering castors (standard trolley comes with 4 braked castors)

#### **Models**

2000-V21	Standard75" x 25.2"
2000S-V21	Short 63" x 25.2"
2000L-V21	Long 83" x 25.2"
2000W-V21 Wide	77" x 27.4"



Side raile on bed side fold to horizontal position. Side rail on caregiver side fold all the way down for easier access to patient.



Bumper wheel protection in all four corners as standard.

#### **Dimensions standard** (in)



