



# EZ1000 Battery Operated Shower Chair

## Specifications for EZ1000 Battery Operated Shower Chair

- Equipment shall be delivered 100% assembled and ready for use after charging the battery
- Equipment is electrically height-adjustable and tiltable for caregiver's ergonomic use and is specifically designed and manufactured for safe in-patient hospital use
- Tilting range from 25 degrees reclining to 7 degrees forward
- Shower chair chassis design to create possibilities for toileting over standard toilets
- Handheld control unit for height settings, recline and forward tilting, for caregiver convenience
- Shower chair to be designed for smooth and safe patient transfers from sling hoists and standing/raising aids
- Shower chair to include a hip belt for patient safety
- Shower chair to be equipped with an adjustable headrest for head and neck comfort, support and security
- Foldable armrests with grip knobs for residents comfort and safety
- Shower chair equipped with emergency stop
- Shower chair equipped with four twin castors with brakes for safe and easy patient transport
- 24 V Lithium Ion removable and rechargeable batteries to be charged via main supply and with visible low battery indicator
- All electronics on the Shower Chair to be in the protection class IPX6 or higher
- Minimum of 45 up-down movements with fully charged batteries with a 150 kg/440 lbs. load
- Seating surfaces shall be made of a soft, durable material that is non water absorbent, easy to clean, disinfect and comfortable to sit on
- Anti-corrosion treatment on all sheet metal parts

Specification text to add for options/accessories if needed

- Shower chair to include a bedpan (lid included)
- Shower chair to be equipped with adjustable and foldable footrest for security and comfort for residents
- Shower chair to include front closing armrest for extra patient safety
- Shower chair to include a chest belt for additional security and support for patient

Dimension and load specifications

- Weight Limit (patient): 200 kg/440 lbs.
- Operating Height Range: Min: 535 mm/21 inch Max: 935 mm/36-4/5 inch
- Width Seating Area: Min: 500 mm/19-2/3 inch Max: 550 mm/21-2/3 inch
- Depth Seating Area: Min: 430 mm/16-4/5 inch Max: 450 mm/17-2/3 inch
- External Width: Max: 700 mm/27-1/2 inch
- Castor Diameter: Min: 100 mm